

CLEVERTRONICS CLP CLEVERFIT PRO EXIT



PRODUCT INFORMATION

Catalogue Number	CCFPRO
Description	CLP Premium Cleverfit PRO Emergency Exit
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Battery Nominal Voltage	3.2V
Battery Capacity	3200mAh
IEC 62620 Battery/Cell Designation	IFpR/27/66[1P1S]M/0+60/80
Charging Method	Intelligent Current Limited Constant Voltage
Charge Current & Voltage	200mA, 3.5V (Max)
Discharge Current at 3.2V (Nominal)	580mA
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Rated Lamp Voltage	100mA, 20.4V
Rated Supply Current	30mA (Standby), 42mA (Max)
Rated Lamp/Module Wattage	2.0 Watts
Power Factor	0.5
Power Consumption	3.7 Watts (Standby), 4.8 Watts (Max)

CLP LITHIUM IRON
PHOSPHATE
PREMIUM
PROVEN PROJECT PERFORMANCE

UK2018-DS-08

clevertronics-uk.co.uk

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003095	PCA:C10622-Lx, Firmware 6C70, NO-CTP

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.