

## CLEVERTRONICS CLP ULTRABLADE PRO



## PRODUCT INFORMATION

Catalogue Number	CUBPRO-ZW
Description	CLP Premium Ultrablade Pro Blade Exit
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	50mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Battery Nominal Voltage	3.2V
Battery Capacity	3200mAh
IEC 62620 Battery/Cell Designation	IFpR/27/66[1P1S]M/0+60/80
Charging Method	Intelligent Current Limited Constant Voltage
Charge Current & Voltage	500mA, 3.5V (Max)
Discharge Current at 3.2V (Nominal)	370mA
Diffuser	All directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Rated Lamp Voltage	60mA, 18V
Rated Supply Current	21mA (Standby), 41mA (Max)
Rated Lamp/Module Wattage	1.1 Watts
Power Factor	0.4
Power Consumption	1.8 Watts (Standby), 3.9 Watts (Max)



UK2018-DS-08

clevertronics-uk.co.uk



## PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> </ul>			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598.2.22, BS 5266			

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
CUBPRO-CKIT-60	Ultrablade Pro,Control Only, LP
8001450	PCA:Powerline Node ZW, #CT10310-A6

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.